

Resisto DALI

Resisto 1500 IP66 DALI 7600lm 840

0010260

Image not found.

Características del producto

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 7600lm; 55W; 138lm/W; 4000K; SDCM<5; DALI dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark.

DESCRIPCIÓN DEL PRODUCTO

Nombre del producto	Resisto 1500 IP66 DALI 7600lm 840
Tecnología	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montaje	Ceiling surface mounting, Suspended, Wall surface mounted
General application	Logistics & Industry
ETIM Class	EC002892
FI del número electrónico	4357068
Warranty	5 years
Fixture luminous flux (lm)	7600
Luminaire efficacy (lm/W)	138
Temperatura de color (K)	4000
IRC (Ra)	80
Variación de color inicial tras el incendio (SDCM)	SDCM5
Colour Consistency (SDCM)	5
Beam Angle (°)	110
Glare control	< 25
Grupo de riesgo fotobiológico	RG1
Consumo total de energía (W)	55
Electrical protection	Class I
Tipo de sistema de control	LED driver constant current
Dimmable	Sí
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Color carcasa luminaria	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288102603
Dimming method	DALI

TABLA DE DATOS

Informacion General

Nombre del producto	Resisto 1500 IP66 DALI 7600lm 840
Tecnología	LED

Resisto DALI

Resisto 1500 IP66 DALI 7600lm 840

0010260

Cap/Base	N/A
Housing	PC Polycarbonate
Montaje	Ceiling surface mounting, Suspended, Wall surface mounted
General application	Logistics & Industry
Operating temperature range (°C)	-20°C - 40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
FI del número electrónico	4357068
Warranty	5 years

Datos ópticos

Fixture luminous flux (lm)	7600
Luminaire efficacy (lm/W)	138
Temperatura de color (K)	4000
IRC (Ra)	80
Variación de color inicial tras el incendio (SDCM)	SDCM5
Colour Consistency (SDCM)	5
Beam Angle (°)	110
Distribution type	Diffuse
Glare control	< 25
Grupo de riesgo fotobiológico	RG1

Datos eléctricos

Consumo total de energía (W)	55
Tensión de red (V)	220-240V
Lamp power factor	0.99
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	9
Electrical protection	Class I
Tipo de sistema de control	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	Sí
Minimum dimming level (%)	1
Drive current (mA)	350
Corriente de irrupción (A)	23.1
Duración de irrupción	174
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Luminarias máximas por 10A C Interruptor automático	21
Max. Luminaires per 13A C Breaker	28
Luminarias máximas por 16A C Interruptor automático	35
Max. Luminaires per 20A C Breaker	45
Max. Luminaires per 10A B Breaker	13

Resisto DALI

Resisto 1500 IP66 DALI 7600lm 840

0010260

Max. Luminaires per 13A B Breaker	17
Max. Luminaires per 16A B Breaker	21
Max. Luminaires per 20A B Breaker	27

Información de vida útil

Vida útil media - L70 B50	100000
Vida media - L80/B20	69000
Vida media - L90/B10	31000

Datos físicos

Color carcasa luminaria	Grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Longitud (mm)	1500
Anchura (mm)	87
Nominal Product Height (mm)	80
Peso (kg)	2.01

Empaquetado

Descripción del paquete	Carton
Product EAN number	5410288102603
Longitud del embalaje individual(cm)	150.5
Anchura única del embalaje (cm)	10.0
Packaging single depth (cm)	8.5
DUN14 (outer)	05410288102603
Cantidad del embalaje por cajas	1
Packaging outer length / height (cm)	150.5
Packaging outer width (cm)	10.0
Packaging outer depth (cm)	8.5

Información de seguridad

Condiciones óptimas de funcionamiento (°C)	-20-40
--	--------

FOTOMETRÍA

DIBUJOS TÉCNICOS