



YDRQ2.E168970 Tubing, Mechanical Protection and Fittings - Component

[Page Bottom](#)

Tubing, Mechanical Protection and Fittings - Component

[See General Information for Tubing, Mechanical Protection and Fittings - Component](#)

REIKU GMBH

E168970

Robert-Bosch-Strasse 3
51674 Wiehl-Bomig, GERMANY

Cat. No.	Max Working Temp, °C	Indoor Use	Outdoor Use
Thermoplastic tubings			
PARE(b)-10F, PARE(b)-12F, PARE(b)-14F, PARE(b)-17F, PARE(b)-23F, PARE(b)-29F, PARE(b)-36F, PARE(b)-48F, PARE(b)-52G, PARE(c)-70G			
	105	Yes	-
PARF(c)-17G, PARF(c)-23G, PARF(c)-29G, PARF(c)-36G, PARF(c)-48G, PARF(c)-52G			
	105	Yes	-
PARN(b)-12F, PARN(b)-14F, PARN(b)-17F, PARN(b)-17G, PARN(b)-23F, PARN(b)-23G, PARN(b)-29F, PARN(b)-29G, PARN(b)-36F, PARN(b)-36G, PARN(b)-48F, PARN(b)-48G, PARN(b)-52G, PARN(b)-70G, PARN(b)-95G			
	105	-	Yes
PARV(b)-17G, PARV(b)-23G, PARV(b)-29G, PARV(b)-36G, PARV(b)-48G, PARV(b)-70G, PARV(b)-95G			
	105	Yes	-
PURM(c)-70G	105	Yes	-
PURR(c)-52G, PURR(c)-70G	105	Yes	-
PURV(c)-52G, PURV(c)-70G	105	Yes	-

Cat. No.	Indoor Dry Locations	Liquid-tight Locations
Thermoplastic fittings		
PA(d)(g)(b)-07(e), PA(d)(g)(b)-10(e), PA(d)(g)(b)-12(e), PA(d)(g)(b)-17(e), PA(d)(g)(b)-23(e), PA(d)(g)(b)-29(e), PA(d)(g)(b)-36(e), PA(d)(g)(b)-48(e), PA(d)(g)(b)-52(e), PA(d)(g)(b)-70(e)		
	-	Yes
PA(d)(g)(b)-07(e), PA(d)(g)(b)-10(e), PA(d)(g)(b)-12(e), PA(d)(g)(b)-17(e), PA(d)(g)(b)-23(e), PA(d)(g)(b)-29(e), PA(d)(g)(b)-36(e), PA(d)(g)(b)-48(e), PA(d)(g)(b)-52(e), PA(d)(g)(b)-70(e)		
	Yes	-
PA(d)(g)(b)-07(e), PA(d)(g)(b)-10(e), PA(d)(g)(b)-12(e), PA(d)(g)(b)-17(e), PA(d)(g)(b)-23(e), PA(d)(g)(b)-29(e), PA(d)(g)(b)-36(e), PA(d)(g)(b)-48(e), PA(d)(g)(b)-52(e), PA(d)(g)(b)-70(e), PA(d)(g)(b)-95(e)		
	-	Yes
PA(d)(g)(b)-07(e), PA(d)(g)(b)-10(e), PA(d)(g)(b)-12(e), PA(d)(g)(b)-17(e), PA(d)(g)(b)-23(e), PA(d)(g)(b)-29(e), PA(d)(g)(b)-36(e), PA(d)(g)(b)-48(e), PA(d)(g)(b)-52(e), PA(d)(g)(b)-70(e), PA(d)(g)(b)-95(e)		
	-	Yes
PM(d)(a)(b)-10(e), PM(d)(a)(b)-12(e), PM(d)(a)(b)-17(e), PM(d)(a)(b)-23(e), PM(d)(a)(b)-29(e), PM(d)(a)(b)-36(e), PM(d)(a)(b)-48(e)		
	-	Yes
PM(d)(a)(b)-10(e), PM(d)(a)(b)-12(e), PM(d)(a)(b)-17(e), PM(d)(a)(b)-23(e), PM(d)(a)(b)-29(e), PM(d)(a)(b)-36(e), PM(d)(a)(b)-48(e)		
	-	Yes
PM(d)(a)(b)-12(e), PM(d)(a)(b)-17(e), PM(d)(a)(b)-23(e), PM(d)(a)(b)-29(e), PM(d)(a)(b)-36(e), PM(d)(a)(b)-48(e)		
	Yes	-
PM(d)(a)(b)-12(e), PM(d)(a)(b)-17(e), PM(d)(a)(b)-23(e), PM(d)(a)(b)-29(e), PM(d)(a)(b)-36(e), PM(d)(a)(b)-48(e)		
	-	Yes

VM(d)(f)(b)-12(e), VM(d)(f)(b)-17(e), VM(d)(f)(b)-23(e), VM(d)(f)(b)-29(e), VM(d)(f)(b)-36(e), VM(d)(f)(b)-48(e)		
	Yes	-
VM(d)(f)(b)-12(e), VM(d)(f)(b)-17(e), VM(d)(f)(b)-23(e), VM(d)(f)(b)-29(e), VM(d)(f)(b)-36(e), VM(d)(f)(b)-48(e)		
	Yes	-
VM(d)(f)(b)-12(e), VM(d)(f)(b)-17(e), VM(d)(f)(b)-23(e), VM(d)(f)(b)-29(e), VM(d)(f)(b)-36(e), VM(d)(f)(b)-48(e)		
	-	Yes
VM(d)(f)(b)-17(e), VM(d)(f)(b)-23(e), VM(d)(f)(b)-29(e), VM(d)(f)(b)-36(e), VM(d)(f)(b)-48(e)		
	-	Yes
VP(d)(f)(b)-10(e), VP(d)(f)(b)-12(e), VP(d)(f)(b)-17(e), VP(d)(f)(b)-23(e), VP(d)(f)(b)-29(e), VP(d)(f)(b)-36(e), VP(d)(f)(b)-48(e)		
	Yes	-
VP(d)(f)(b)-10(e), VP(d)(f)(b)-12(e), VP(d)(f)(b)-17(e), VP(d)(f)(b)-23(e), VP(d)(f)(b)-29(e), VP(d)(f)(b)-36(e), VP(d)(f)(b)-48(e)		
	Yes	-
VP(d)(f)(b)-17(e), VP(d)(f)(b)-23(e), VP(d)(f)(b)-29(e), VP(d)(f)(b)-36(e), VP(d)(f)(b)-48(e)		
	-	Yes
VP(d)(f)(b)-23(e), VP(d)(f)(b)-29(e), VP(d)(f)(b)-36(e), VP(d)(f)(b)-48(e)		
	-	Yes

(a) - Represents O for no inner seal or V for both outer flat washer and inner seal

(c) - Represents B for black

(d) - Represents G, B, W, S, A, I or F for the fitting design

(e) - Represents various codes, or be blank, for the thread details

(f) - Represents R for inner seal or V for both outer flat washer and inner seal

(g) - Represents O for no inner seal, V for both outer flat washer and inner seal or D for both outer flat washer and inner seal on larger sizes

Marking: Company name, catalog designation and temperature rating on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2017-03-31

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".