

 C e m b r e		IDENTIFICATION & LABELLING SYSTEMS		PDS 0031	
DATA SHEET					
APPLICABLE PRODUCTS: MG-VTR-R					
Part code			Colour		RAL/Pantone
48900, 48901, 48902, 48903, 48913, 48928			White		-
48400, 48401, 48402, 48403, 48413, 48428			Yellow		-
48700, 48701, 48702, 48703, 48713, 48728			Metallic Grey		-
TECHNICAL CHARACTERISTICS					
Criterion			Detail		
Material type			Polyvinylchloride (PVC)		
Material self-extinguishing class			Class V0 (UL 94)		
Material Halogen free			NO		
Adhesive type			-----		
Adhesive application temperature range (°C)			-----		
Adhesive adhesion on Stainless Steel (N/m)			-----		
Total thickness of medium (mm)			0,50		
Medium operating temperature range (°C)			-30 ÷ +80		
RoHS compliant			YES		
TEST DATA					
Reference		Scope		Result	
UNI EN ISO 4892-2		UV resistance (Standard test 500 h)		Compliant	
CEI 16-7		Thermal resistance		Compliant	
CEI 16-7		Print integrity		Compliant	
IEC 61439-1:2009 clause 10.2.7		Print integrity		Compliant	
CEI 23-11 (CEI EN 61058-1)		Print integrity		Compliant	
CEI EN 61010-1 (VDE 0411-1)		Print integrity		Compliant	
CEMBRE internal standard (alcohol applied)		Print integrity		Compliant	
NOTES: Test media were printed with original Cembre ribbons on Cembre printing systems.					
Rev.	Date	Purpose of revision	Compiled by	Verified by	Approved by
0.0	11/12/2009	First version	F. Bortot	A. Seno	E. Peroni

CEMBRE SpA reserves the right to modify and improve products without notice.