




C/ Río Jarama nº 149
45007, Toledo.
Tel.: 925 23 38 12
Fax: 925 23 38 80

www.grupoprilux.com




Icon 6W

BASIC



H (m)	D (m)	E _{max} (lx)
1	2.36	184
2	4.73	46
3	7.09	20
4	9.45	12



icon basic 6W

CÓDIGO	CEE	POTENCIA	FLUJO	CCT	CASQUILLO	DIMENSIONES
378680	A+	6W	472lm	3.000K	GU10	Ø50 x 58mm
386319	A+	6W	491lm	4.000K	GU10	Ø50 x 58mm
378697	A+	6W	508lm	5.000K	GU10	Ø50 x 58mm




TENSIÓN: 230V
INTENSIDAD: 51mA
FRECUENCIA: 50-60Hz
Cosφ: >0.55
Ta: -10 ~ +40° C
ÁNGULO: 100°
Ra: >80
VIDA MEDIA: 15.000h

VOLTAGE: 230V
CURRENT: 51mA
FREQUENCY: 50-60Hz
Cosφ: >0.55
Ta: -10 ~ +40° C
ANGLE: 100°
Ra: >80
LIFETIME: 15.000h

TENSION D'ALIMENTATION: 230V
FRÉQUENCE: 50-60Hz
INTENSITÉ: 51mA
Cosφ: >0.55
Ta: -10 ~ +40° C
ANGLE D'OUVERTURE: 100°
Ra: >80
HEURES DE VIE: 15.000h

TENSÃO: 230V
FREQUÊNCIA: 50-60Hz
INTENSIDADE: 51mA
Cosφ: >0.55
Ta: -10 ~ +40° C
ÂNGULO DE ABERTURA: 100°
Ra: >80
VIDA: 15.000h






C/ Río Jarama nº 149
45007, Toledo.
Tel.: 925 23 38 12
Fax: 925 23 38 80


www.grupoprilux.com



Icon 6W BASIC



H (m)	D (m)	E _{max} (lx)
1	2.52	212
2	5.04	53
3	7.56	24
4	10.08	13



icon basic 6W 5.000K

CÓDIGO	CEE	POTENCIA	FLUJO	CCT	CASQUILLO	DIMENSIONES
381826	A+	6W	466lm	3.000K	GU5.3	Ø50 x 47mm
386302	A+	6W	498lm	4.000K	GU5.3	Ø50 x 47mm
381833	A+	6W	532lm	5.000K	GU5.3	Ø50 x 47mm



TENSIÓN: 12V ac
INTENSIDAD: 500mA
FRECUENCIA: 50/60Hz
Cosp: >1
Ta: -10 ~ +40° C
ÁNGULO: 100°
Ra: >80
VIDA MEDIA: 25.000h

VOLTAGE: 12V ac
CURRENT: 500mA
FREQUENCY: 50/60Hz
Cosp: >1
Ta: -10 ~ +40° C
ANGLE: 100°
Ra: >80
LIFETIME: 25.000h

TENSION D'ALIMENTATION: 12V ac
FRÉQUENCE: 50/60Hz
INTENSITÉ: 500mA
Cosp: >1
Ta: -10 ~ +40° C
ANGLE D'OUVERTURE: 100°
Ra: >80
HEURES DE VIE: 25.000h

TENSÃO: 12V ac
FREQUENCIA: 50/60Hz
INTENSIDADE: 500mA
Cosp: >1
Ta: -10 ~ +40° C
ÂNGULO DE ABERTURA: 100°
Ra: >80
VIDA: 25.000h

