



Color: blanco

Datos técnicos	
Adecuado	para sección de conductor: 1 ... 2,5 mm²
Método de marcaje	Termotransferencia
Montaje	Roll
Preconfeccionado	20 m/rollo
Dispositivo de marcaje	Smart Printer (impresora compacta por termotransferencia)

Datos geométricos	
Profundidad	0,185 mm

Datos mecánicos	
Tipo de montaje	Deslizante
Relación de contracción	2:1
Resistencia a las manchas	en combinación con tira 258-5005

Datos de material	
Color	blanco
Material	Poliolefina
Resistencia a rayos UV	EN 60068-2-5:2010, procedimiento B
Información de adhesivo	without adhesive
Libre de halógenos	Sí
Peso	217,1 g
Carga de fuego	0 MJ



Requisitos medioambientales		
Temperatura de aire circundante (almacenamiento)		+10 ... +25 °C
Temperatura ambiente (funcionamiento)		-55 ... +125 °C
Humedad relativa		45 ... 55 %

Datos comerciales		
PU (SPU)		1 UDS
Tipo de embalaje		Box
País de origen		DK
GTIN		4055143370240
Número de arancel aduanero		39173200900

Product Classification		
UNSPSC		39121705
eCl@ss 10.0		27-40-04-01
eCl@ss 9.0		27-40-04-01
ETIM 9.0		EC001530
ETIM 10.0		EC001530
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Descargas		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance 211-502		

Documentation			
Operating Instructions			
211-502 Information on printing material	1 28.08.2020	pdf 1059.74 KB	